



HYPERION

2025-2026 LED Product Line

LED Lamps



Lamp Type	A19
Wattage	5.5/9/12/14
Lumens	450/800/1100/1500
Dimmable	No/Yes
Colour Temp.	2700/3000/5000 DK
Life (Hours)	10,000/15,000



Lamp Type	PAR 30 Long Neck
Wattage	12
Lumens	840
Dimmable	Yes
Colour Temp.	2700/3000/5000 DK
Life (Hours)	25,000



Lamp Type	BR 30
Wattage	9
Lumens	650
Dimmable	No/Yes
Colour Temp.	2700/3000/5000 DK
Life (Hours)	10,000/15,000



Lamp Type	PAR 30 Short Neck
Wattage	12
Lumens	750
Dimmable	Yes
Colour Temp.	2700/3000/5000 DK
Life (Hours)	25,000



Lamp Type	PAR 20
Wattage	7
Lumens	500
Dimmable	Yes
Colour Temp.	2700/3000/5000 DK
Life (Hours)	25,000



Lamp Type	PAR 38
Wattage	13
Lumens	900/910
Dimmable	No/Yes
Colour Temp.	2700/3000/5000 DK
Life (Hours)	10,000/25,000



Lamp Type	PAR 16 ES
Wattage	7
Lumens	500
Dimmable	Yes
Colour Temp.	2700/3000/5000 DK
Life (Hours)	25,000



Lamp Type	PAR 20 ES
Wattage	7
Lumens	500
Dimmable	Yes
Colour Temp.	2700/3000/5000 DK
Life (Hours)	25,000



Lamp Type	MR 16 (GU 5.3/GU10)
Wattage	5/7
Lumens	380/520
Dimmable	Yes
Colour Temp.	2700/3000/5000 DK
Life (Hours)	25,000



Lamp Type	PAR 30 ES
Wattage	12
Lumens	840
Dimmable	Yes
Colour Temp.	2700/3000/5000 DK
Life (Hours)	25,000



Lamp Type	PAR 38 ES
Wattage	15.5/16/16.5
Lumens	1280/1450/1600
Dimmable	Yes
Colour Temp.	2700/3000/5000 DK
Life (Hours)	25,000

Downlights



Product	Slim Downlight
Size (Inch)	3/4/6/8/12
Shapes	Circular/Square
Wattage	6/9/12/15/18/24
Colour Temp.	2700-5000 DK
Life (Hours)	50,000



Gimbal

Product	Gimbal
Size (Inch)	3/4/6
Shapes	Circular/Square
Wattage	9/12
Colour Temp.	2700-5000 DK
Life (Hours)	50,000

Recessed Retrofit



Product	Recessed Retrofit
Size (Inch)	4/5/6
Shapes	Circular/Square
Wattage	9.5/10.8/11.5/15/20
Trim	Open/Baffled
Colour Temp.	2700/3000/5000 DK
Life (Hours)	35,000



T8 Tubes

Product	T8 Tubes
Wattage	14/18/22
Lumens	1600/2800
Dimmable	No
Colour Temp.	4000/5000/6500 DK
Life (Hours)	32,000
Voltage	100-277 & Instant Fit

Corn Bulbs



Product	Corn Bulb
Wattage	36/54/75/100/120
Lumens/Watt	135/125
IP Rating	64
Colour Temp.	2700-6500 DK
Life (Hours)	50,000



Retrofit Lamps

Product	Retrofit Lamp
Wattage	27/36/54/75/95/115
Lumens/Watt	108/118
IP Rating	51
Colour Temp.	4000/5000/5700 DK
Life (Hours)	50,000

UFO High/Low Bay



Product	UFO Hi/Low Bay
Wattage	100/150/200/240
Lumens/Watt	130/150
Voltage	100-277/347/480
Colour Temp.	3000-6300 DK
Life (Hours)	50,000
Reflector	Acrylic/Aluminum

Floodlights



Product	Floodlights
Wattage	30/50/80/100/150/200
Lumens/ W	120/140
IP Rating	65
Colour Temp.	30000-6500 DK
Life (Hours)	50,000

Canopy



Product	Canopy Light
Wattage	45/50/65/70/80/100
Lumens/Watt	120/139
Voltage	100-277
Colour Temp.	4000-5700 DK
Life (Hours)	30,000

Pole Lights



Product	Pole Lights
Wattage	100/150/200/250/300
Lumens/W	140
Voltage	90-305/347-480
Colour Temp.	2700-6500 DK
Life (Hours)	50,000

Wall Packs



Product	Mini Wall Pack
Wattage	12/15/18/25/26
Lumens/Watt	120/130
IP Rating	65
Colour Temp.	4000-6500 DK
Life (Hours)	50,000
Voltage	100-277/347-480



Product	Moon Wall Pack
Wattage	40/60/80/100
Lumens/ W	120/140
IP Rating	65
Colour Temp.	4000/5700
Life (Hours)	50,000
Dimmable	Yes (0-10V)
Voltage	100-277/347-480



Product	Wall Pack Std.
Wattage	30/45/60/80/100
Lumens/Watt	120
IP Rating	65/67
Colour Temp.	4000-5700 DK
Life (Hours)	50,000
Dimmable	Yes (0-10V)
Voltage	100-277/347-480

Vapour Tight



Product	Vapour Tight
Wattage	30/60/90/120/180
Lumens/Watt	156
Voltage	120-277/347/480
Colour Temp.	3000-6200 DK
Life (Hours)	50,000

Linear



Product	Linear
Wattage	30/40
Lumens/ W	115/156
Voltage (Vac)	100-277/347-480
Colour Temp.	2900-5300 DK
Life (Hours)	50,000
Dimmable	Yes (0-10V)

Flat Panels



Product	Flat Panels
Sizes (Feet)	1X4/ 2X2/2X4
Wattage	30/40/45/55/60/70
Lumens/ Watt	100/125
Colour Temp.	3000-6000 DK
Life (Hours)	50,000
IP Rating	65

Troffers



Product	Troffers
Sizes (Feet)	2X2/2X4
Wattage	20/24/30/40/50
Lumens/ Watt	130/150
Colour Temp.	3000-5000 DK
Life (Hours)	50,000
Dimmable	Yes (0-10V)

ARCHITECTURAL OFFERINGS



Stadium & High Mast Lighting



Product	Stadium & HM
Design Type	Modular
Wattage	100-1000
Lumens/Watt	130
Voltage (Vac)	100-305
Life (Hours)	50,000
Beam Angle D.	15/40/60/90/30X70



Product	Stadium & HM
Design Type	High Efficiency
Wattage	100-1000
Lumens/Watt	170
Voltage (Vac)	90-305
Life (Hours)	50,000
Beam Angle D.	10/25/40/60/90

Horticulture



Product	Horticulture
Design Type	Modular
Wattage	100-500
IP Rating	66
Voltage (Vac)	100-277
Life (Hours)	60,000
Beam Angle D.	90X90 /144X62



Product	Horticulture
Design Type	Linear
Wattage	50-300
IP Rating	67
Voltage (Vac)	100-277
Life (Hours)	50,000
Beam Angle D.	40/60/90/150X75



Product	Horticulture
Design Type	Series
Wattage	400/640/800
Voltage (Vac)	100-277
Life (Hours)	50,000
PPF Efficacy	2.3umol/j

LED Emergency



Product	Emergency Light
LED Design	Multiple, various colors & languages
Application	Indoor/Outdoor
Back Up (In Minutes)	Standard 90m/Non Standard as desired
Voltage (Vac)	120/347
Operating Temp D C	-10 to +50
Wattage	3 W Standard/ Non Standard as desired

Wrap Fixture



Product	Wrap Fixture
Sizes (Feet)	2/4
Wattage	20/26/40
Lumens/ Watt	120/145
Colour Temp.	3500/4000/5000 DK
Life (Hours)	50,000
Voltage	100-277
Dimming	(0-10V)

